

## **DECLARATION of PERFORMANCE**

1. Unique identification code of the product type:

0/2 FP Washed Plastering Sand Gf85

2. Intended use: Aggregates for Mortar

3. Manufacturer: Mansfield Sand Company Ltd.

Two Oaks Quarry, Coxmoor Road, Sutton in Ashfield, Nottinghamshire NG17 5LZ

4. AVCP: System 4

5. Designated Standard: BS EN 13139

6. Declared performance:

Essential characteristics	Performance
Particle Size:	0/2
Fines Content:	f3
Fines Quality:	NPD
Particle Shape:	NPD
Shell Content:	NPD
Particle Density:	2.74%
Water Absorption:	0.20%
Chlorides:	NPD
Acid Soluble Sulfates:	$AS_{0.2}$
Total Sulfur:	< 0.01%
Constituents which alter the rate of settling and hardening of mortar:	NPD
Durability against alkali-silica reactivity:	NPD
Durability against freeze/thaw:	NPD
Emissions of Radioactivity:	NPD
Release of Heavy Metals:	NPD
Release of Polyaromatic Hydro Carbons:	NPD
Release of Other Dangerous Substances:	NPD

Mansfield Sand Company Ltd confirm that the product identified, is in conformity of the declared performance and complies with the requirements of BS EN 13139 including annex ZA attestation of conformity system 4.

Signed for and on behalf of the Mansfield Sand Company Ltd:	
Andrew Ward	A. Ward
Technical Manager	19.10.23



## Mansfield Sand Company Ltd. Two Oaks Quarry, Coxmoor Road, Sutton in Ashfield, Nottinghamshire, NG17 5LZ.

02

## **BS EN 13139 Aggregates for Mortar**

## 0/2 FP Washed Plastering Sand Gf85

Particle Size:	0/2
Fines Content:	f3
Fines Quality:	NPD
Particle Shape:	NPD
Shell Content:	NPD
Particle Density:	2.74%
Water Absorption:	0.20%
Chlorides:	NPD
Acid Soluble Sulfates:	$AS_{0.2}$
Total Sulfur:	< 0.01%
Constituents which alter the rate of settling and hardening of mortar:	NPD
Durability against alkali-silica reactivity:	NPD
Durability against freeze/thaw:	NPD
Emissions of Radioactivity:	NPD
Release of Heavy Metals:	NPD
Release of Polyaromatic Hydro Carbons:	NPD
Release of Other Dangerous Substances:	NPD
_	