

## **DECLARATION of PERFORMANCE**

No. 19659

1. Unique identification code of the product type:

Aggregate Concrete Masonry Unit 20N OPC Brickslips - 215mm

2. Intended use: Walls, columns and partitions

3. Manufacturer:

Mansfield Sand Company Ltd (Brick Division).

**Crown Farm Way** 

**Forest Town** 

Mansfield

**Nottinghamshire** 

**NG19 0FT** 

4. AVCP: System 4

5. Designated Standard: BS EN 771-3

6. Declared performance:

Essential characteristics		Performance
	Length mm	215
Dimensions	Width mm	100
	Height mm	40
	Tolerance Category	D1
Configuration		Group 1
	Mean	$20N/mm^2$
Compressive	Direction of Load	Bed face
strength	Unit category	Category 11
Dimension Stability		NPD
Bond	Shear bond strength	0.15N/mm <sup>2</sup> (tabulated value)
strength	Flexural bond strength	NPD
Reaction to fire		A1
		(Commission Decision 2000/605/EC)
Water Absorption		NPD
Water vapour permeability		5/15 (tabulated value)
Direct airborne sound insulation		
Gross Density		$2,000 \text{ kg/m}^3$
Configuration; dimensions and tolerances		Group 1
Thermal conductivity		1.00 W/(mK) [ $\lambda_{10,dry}$ ] (tabulated value)
Durability against freeze/thaw		Not to be left exposed

Mansfield Sand Company Ltd (Brick Division) confirm that the product identified, is in conformity of the declared performance and complies with the requirements of BS EN 771-3 including annex ZA attestation of conformity system 4.

Signed for and on behalf of the Mansfield Sand Company Ltd:



Mansfield Sand Company Ltd (Brick Division). Crown Farm Way, Forest Town, Mansfield, Nottinghamshire, NG19 0FT

13

19659

## **BS EN 771-3**

**Product: Aggregate Concrete Masonry Unit 20N OPC Brickslips – 215mm** 

Intended use: Walls, columns and partitions

Dimensions: L:215mm, W:100mm, H:40mm

**Dimension tolerances** 

Category: D1

Configuration: Group 1

Compressive strength: mean 20N/mm<sup>2</sup>

Reaction to fire: A1

Water Absorption: NPD

Water vapour diffusion: 5/15

**Direct airborne sound insulation:** 

Gross dry density: 2,000 kg/m<sup>3</sup>

Thermal conductivity:  $1.00 \text{ W/(mK)} [\lambda 10, \text{dry}]$ 

Durability against freeze/thaw: Not to be left exposed