

## **DECLARATION of PERFORMANCE**

No. 19810

- 1. Unique identification code of the product type: Aggregate Concrete Masonry Unit 7.3N Medium Dense CL Block 530mm x140mm
- 2. Intended use: In block and beam floor systems
- Manufacturer: Mansfield Sand Company Ltd (Brick Division). Crown Farm Way Forest Town Mansfield Nottinghamshire NG19 0FT
  AVCD: System 4
- 4. AVCP: System 4
- 5. Designated Standard: BS EN 771-3
- 6. Declared performance:

Essential characteristics		Performance
	Length mm	530
Dimensions	Width mm	140
	Height mm	140
	Tolerance Category	D1
Configuration		Group 1
	Mean	7.3N/mm <sup>2</sup>
Compressive	Direction of Load	Bed Face
strength	Unit category	Category 11
Dimension Stability		NPD
Bond	Shear bond strength	$0.15 \text{N/mm}^2$ (tabulated value)
strength	Flexural bond strength	NPD
Reaction to fire		A1
		(Commission Decision 2000/605/EC)
Water Absorption		NPD
Water vapour permeability		5/15 (tabulated value)
Direct airborne sound insulation		
Gross Density		1,575 kg/m <sup>3</sup>
Configuration; dimensions and tolerances		Group 1
Thermal conductivity		0.81 W/(mK) [ $\lambda_{10,dry}$ ] (tabulated value)
Durability against freeze/thaw		Not to be left exposed

Mansfield Sand Company Ltd (Brick Division) confirm that the product identified, is in conformity of the declared performance and complies with the requirements of BS EN 771-3 including annex ZA attestation of conformity system 4.

Signed for and on behalf of the Mansfield Sand Company Ltd:

Andrew Ward Technical Manager

...A.Ward..... 09.08.22

## UK CA

## Mansfield Sand Company Ltd (Brick Division). Crown Farm Way, Forest Town, Mansfield, Nottinghamshire, NG19 0FT

13

19810

## BS EN 771-3

**D1** 

NPD

 $1,575 \text{ kg/m}^3$ 

Product: Aggregate Concrete Masonry Unit 7.3N Medium Dense CL Block 530mm x140mm

Intended use: In block and beam floor systems

Dimensions:

L:530mm, W:140mm, H:140mm

Dimension tolerances Category:

Water Absorption:

Gross dry density:

Configuration: Group 1

Compressive strength: mean 7.3N/mm<sup>2</sup>

Reaction to fire: A1

Water vapour diffusion: 5/15

Direct airborne sound insulation:

Direct airborne sound insulation:

Thermal conductivity: 0.81 W/(mK) [λ10

Thermal conductivity:0.81 W/(mK) [λ10,dry]

Durability against freeze/thaw: Not to be left exposed