



DECLARATION of PERFORMANCE

No. 19800

1. Unique identification code of the product type:
Aggregate Concrete Masonry Unit 7.3N Medium Dense Tray Tile 440mm
2. Intended use: **In block and beam floor systems**
3. Manufacturer:
Mansfield Sand Company Ltd (Brick Division).
Crown Farm Way
Forest Town
Mansfield
Nottinghamshire
NG19 0FT
4. AVCP: **System 4**
5. Designated Standard: **BS EN 771-3**
6. Declared performance:

Essential characteristics		Performance
Dimensions	Length mm	440
	Width mm	215
	Height mm	100
	Tolerance Category	D1
Configuration		Group 1
Compressive strength	Mean	7.3N/mm ²
	Direction of Load	Bed face
	Unit category	Category 11
Dimension Stability		NPD
Bond strength	Shear bond strength	0.15N/mm ² (tabulated value)
	Flexural bond strength	NPD
Reaction to fire		A1 (Commission Decision 2000/605/EC)
Water Absorption		NPD
Water vapour permeability		5/15 (tabulated value)
Direct airborne sound insulation		1,575 kg/m ³ Group 1
Gross Density		
Configuration; dimensions and tolerances		
Thermal conductivity		0.81 W/(mK) [$\lambda_{10,dry}$] (tabulated value)
Durability against freeze/thaw		Not to be left exposed

Mansfield Sand Company Ltd (Brick Division) confirm that the product identified, is in conformity of the declared performance and complies with the requirements of BS EN 771-3 including annex ZA attestation of conformity system 4.

Signed for and on behalf of the Mansfield Sand Company Ltd:

Andrew Ward
Technical Manager

...*A.Ward*.....
09.08.22



**Mansfield Sand Company Ltd (Brick Division).
Crown Farm Way, Forest Town, Mansfield, Nottinghamshire, NG19 0FT**

13

19800

BS EN 771-3

**Product: Aggregate Concrete Masonry Unit 7.3N Medium Dense T Block
440mm**

Intended use: In block and beam floor systems

Dimensions: L:440mm, W:215mm, H:100mm

Dimension tolerances

Category: D1

Configuration: Group 1

Compressive strength: mean 7.3N/mm²

Reaction to fire: A1

Water Absorption: NPD

Water vapour diffusion: 5/15

Direct airborne sound insulation:

Gross dry density: 1,575 kg/m³

Thermal conductivity: 0.81 W/(mK) [$\lambda_{10,dry}$]

Durability against freeze/thaw: Not to be left exposed