



DECLARATION of PERFORMANCE

No. 19678

1. Unique identification code of the product type:
Aggregate Concrete Masonry Unit 10N OPC Brickslips – 100mm Longslip
2. Intended use: **Walls, columns and partitions**
3. Manufacturer:
Mansfield Sand Company Ltd (Brick Division).
Crown Farm Way
Forest Town
Mansfield
Nottinghamshire
NG19 0FT
4. AVCP: **System 4**
5. Harmonised Standard: **EN 771-3:2011 +A1:2015**
6. Declared performance:

Essential characteristics		Performance
Dimensions	Length mm	385
	Width mm	100
	Height mm	40
	Tolerance Category	D2
Configuration		Group 1
Compressive strength	Mean	10N/mm ²
	Direction of Load	Perpendicular to bed face
	Unit category	Category 11
Dimension Stability		NPD
Bond strength	Shear bond strength	0.15N/mm ² (tabulated value)
	Flexural bond strength	NPD
Reaction to fire		Euroclass A1 (Commission Decision 2000/605/EC)
Water Absorption		NPD
Water vapour permeability		5/15 (tabulated value)
Direct airborne sound insulation		2,000 kg/m ³ Group 1
Gross Density		
Configuration; dimensions and tolerances		
Thermal resistance		1.00 W/(mK) [$\lambda_{10,dry}$] (tabulated value)
Durability against freeze/thaw		NPD

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the manufacturer.

Signed for and on behalf of the Mansfield Sand Company Ltd:

Andrew Ward
Technical Manager

...*A. Ward*.....
16.09.18



**Mansfield Sand Company Ltd (Brick Division).
Crown Farm Way, Forest Town, Mansfield, Nottinghamshire, NG19 0FT**

13

19678

EN 771-3:2011 +A1:2015

**Product: Aggregate Concrete Masonry Unit 10N OPC Brickslips
– 100mm Longslip**

Intended use: Walls, columns and partitions

Dimensions: L:385mm, W:100mm, H:40mm

Dimension tolerances:

Category: D2

Configuration: Group 1

Compressive strength: mean 10N/mm²

Reaction to fire: Euroclass A1

Water Absorption: NPD

Water vapour diffusion: 5/15

Direct airborne sound insulation:

Gross dry density: 2,000 kg/m³

Configuration: Group 1

Durability against freeze/thaw: NPD